

5MP Motorized Zoom IP Vandal Dome Camera w/Active Deterrence w/Full Color w/AI



- 5MP (2880 x 1620) @30FPS Encoding
- H.265/H.264 Video Compression
- Advanced AI (Person/Vehicle, Perimeter, Line Crossing, Cross Counting, Stationary Object, Heat Map, Crowd Density, Queue Length, Rare Sound, License Plate Recognition, Facial Recognition*)
- Active Deterrence (Red/Blue Warning Lights, Siren, Custom Voice)
- Full Color Night Vision / IR Selectable
- True 120db Wide Dynamic Range
- Audio, Built-in Mic and Speaker
- 2.8-12mm Motorized Zoom Lens
- Triple-Stream Recording
- Google Drive/Drop Cloud Support
- NAS and FTP Network Storage
- DDNS
- Micro SD Slot (up to 256GB)
- ONVIF Compatible
- DC12V/PoE Power
- IK10 Vandal Rated
- IP67 Waterproof Rating
- NDAA and FCC Compliant

Technical Specifications

Camera	
Imaging Device	1/2.7", 5.0 Megapixel, Progressive Scan, CMOS
Effective Pixels	5MP 2880(H)x1620(V)
Min. Illumination	Color 0.002Lux @F1.0(AGC ON); B/W 0 lux @ IR ON
Lens Type/Focal Length	2.8-12mm Motorized Zoom Lens
Max Aperture Ratio	F1.0
Angular Field of View	Horizontal:113-35°, Vertical:59-20°, Diagonal: 138-41°
Min. Object Distance	2m
IR LED	2
Warm Light	2
Red/Blue Light	2 (1 Red, 1 Blue)
IR Distance	30m
Warm Light Distance	25m
Wide Dynamic Range	True WDR
Image Setting	Full Color Mode / Day&Night / Schedule

White Balance	Auto/Manual
BLC/HLC	Yes
Electronic Shutter Speed	1/5 ~ 1/20000s
Digital Noise Reduction	3D DNR

Image	
Video Compression	H.265+/H.264+/H.265/H.264
Audio Compression	G.711a
Resolution	"Mainstream: 5MP (2880x1620) @30fps Substream: 720P (1280x720) @30fps Mobilestream: VGA (640x480) @30fps"
Video Quality Adjustment	256Kbps - 8Mbps
Bitrate Control	CBR/VBR

Interfaces	
Network	RJ45 (10/100 Base-T)
Audio	Built-in Microphone and Speaker
Local Storage	Micro SD, up to 256GB
Network Storage	NAS (CIFS/SMB), FTP
Reset Button	Yes
Alarm	n/a

AI/AD	
Smart Motion Detection	Pedestrian, Vehicle, Perimeter Intrusion, Line Crossing
License Plate Recognition	Yes
Facial Recognition	Yes (Requires NVR Support)
Additional AI	Cross Counting, Stationary Object Detection, Heat Map, Crowd Density, Queue Depth, Rare Sound Detection
Active Deterrence	Siren, Red/Blue Strobe, Custom Voice

Functions	
Remote Monitoring	Web Browser, Client VMS, Mobile App
Mobile App	XVM
Network Protocol	IPv4, IPv6, TCP, UDP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, HTTPS, FTP, CIFS, SMB, UPnP, SNMP,
Interface Protocol	ONVIF (Profile S/G/T)
ANR	Yes
Security	IP Address Filter, Complex Password, Authenticated User
Regions of Interest (ROI)	Yes
Corridor Mode	Supported

General	
Power Supply	DC12V/POE
Power Consumption	Max 4.8W, PoE Max 6.3W
PoE	Yes, 802.3af
Ingress Protection	IP67
Dimensions (mm)	149 x 115mm
Working Environment	Temperature: -35°C~ +60° (-31°F ~ 140°F) Humidity: Less than 95% RH
Weight	820g
Material	Metal, IK10 Vandal
NDAA and FCC-Compliant	Yes

